



FICHA TECNICA
TECHNICAL SPECIFICATIONS

Modelo/Model: HCT-25C
Revisión : 0

DATOS ARTICULO / PRODUCT DATA:

DESIGNACION DESIGNATION	DESCRIPCION DESCRIPTION	CODIGO CODE
HCT-25C	CABEZAL CORTA TUERCAS HEAD NUT-SPLITTERS	1705000

DIBUJO/DRAFT



CARACTERISTICAS TECNICAS/TECHNICAL DATA:

FUERZA FORCE	PRESION DE TRABAJO WORKING PRESSURE
135 KN 13.7 TON	700 BAR 10,000 psi

LONGITUD LENGTH	PESO WEIGHT
207 mm.	4 Kg 8.8 lb

(CN) Cortatuercas / Nut-Splitters

Model	Capacity	Length	Weight	Quality	Minimum	Model of nut	Replacement blade	D		L	A	B	C	D	E	F	G	
Modelo	Capacidad	Longitud	Peso	Calidad		Modelo de Tuerca	Cuchilla de Recambio	"	mm	"	mm	mm	mm	mm	mm	mm	mm	
	Kn	mm	Kg	12.9	8.8	5.6												
HCT-25C	135	207	4.0	M24 M27M27 7/8 1 1	M12 1/2	ASTM A 194	CRN.02.24	1/2	12.70	3/4	18.67	65	207	12	30	40	56	0
								7/8	22.22	1 7/16	13.77							
								1	25.40	1 5/8	41.00							
HCT-24A	135	296	5.0	* M24M24 7/8 7/8	M16 5/8	ASTM A 194	CRN.03.24	5/8	15.87	1 5/16	33.33	87	296	-	24	69	62	38
								7/8	22.22	1 7/16	13.77							
AHCT-27C	138	471	4.3	M24 M27M27 7.8" 1" 1"	M12 1/2"	ASTM A 194	CRN.00.24	1/2	12.70	3/4	19.05	68	471	13	51	70	108	-
								7/8	22.22	1 7/16	36.51							
								1	25.40	1 5/8	41.00							
HCT-36C	350	267	11.0	M33 M33M33 2 2 2	M25 1	ASTM A 194	CRN.02.33	3	76.20	4 5/8	117.00	106	267	14	55	60	74	0
								2	50.80	3 1/8	79.00							
HCT-52C	439	388	13.0	M52 M52M52 2 2 2	M36 1-1/2	ASTM A 194	CRN.01.52	1 1/2	38.10	2 3/8	60.00	131	368	17	55	120	136	84
								2	50.80	3 1/8	79.00							
HCT-80C	1134	435	40.0	M80 M80M80 3 3 3	M68 2-1/2"	ASTM A 194	CRN.01.080	2 3/4	69.70	3.75	108.00	185	435	37	90	200	202	120
								3	76.20	4.47	115.00							

DESCRIPCION/DESCRIPTION:

Corta tuercas diseñado para actuar de dos formas diferentes, cortando o deformando las tuercas, según la resistencia del material de las mismas.
La herramienta corta materiales con Resistencia inferior a 500 N/mm² y deforma materiales hasta 1.250 N/mm².
Se conecta por enchufe rápido.

*These tools are designed to work in two different ways, depending on the resistance of the material of the nuts, cutting or deforming them.
The tool cuts materials with a resistance lower than 500 N/mm² and deforms all materials up to a resistance of 1250 N/mm².
Fast coupling connecting*

ENVASADO/PACKAGING:

Caja de transporte / Transport box.